

Recommended Media List

Xerox® Color C60/C70 Press

This Recommended Media List contains Xerox® Paper and Specialty Media that has been extensively tested on the Xerox® Color C60/C70 Press for image quality and performance by Xerox® at the Xerox® Media Technology Center.

The paper and specialty media on this list are approved by Xerox and recommended for use in all configurations of the Xerox® Color C60/C70 Press.

All Xerox® Paper and Specialty Media on this list are digitally optimized, designed and manufactured for optimal performance in Xerox digital printing equipment and carry the Domtar 100% Performance Guarantee. Domtar offers a 100% Performance Guarantee for any Xerox® Paper or Specialty Media that is featured on the Recommended Media List for a specific Xerox printer or digital press. This is your assurance that if you are unhappy with the performance of recommended Xerox® Paper or Specialty Media, Domtar will either take back the unused product and replace it or refund your money – guaranteed.

Domtar Paper Company, LLC. and Domtar Inc., (collectively referred to as “Domtar”), are the exclusive U.S. and Canadian trademark licensees of Xerox® Paper and Specialty Media. Domtar’s and Xerox’s extensive collaborative testing and stringent specifications ensure that we are able to guarantee the performance and consistency of Xerox® Paper and Specialty Media.

Recommended Media List

General Information

Customers should validate that the Best Practices for Operation for the selected Xerox® Paper or Specialty Media are acceptable for their application. When purchasing a particular media product for the first time, customers are advised to purchase small quantities to ensure that expectations are met.

Media observations made in this publication are based on tests conducted using standard images with moderate to heavy image area coverage. Test machines are maintained within specifications defined by user documentation. Where applicable, suggested adjustments and best practices are included to optimize media performance. Note that “size” designation is for sheet dimensions only, and is not used to indicate grain direction.

The Stock Library Montage application can be updated with the most current Recommended Media List by downloading the “Recommended Media List.rml” file from Xerox.com. This file can be found on Xerox.com under the Support and Drivers tab, searching on Color Press. Instructions on how to update the Stock Library Manager media list are included with the file.

To view the most current Recommended Media List, please visit www.xeroxpaperusa.com/resources/recommended-media-list.

Warranty Disclaimer

Domtar and Xerox make no guarantees or warranties, either expressed or implied, concerning the performance, use or replacement of non-Xerox branded media or throughput products. Customers should inquire directly of their paper distributor or manufacturer for any guarantees they may offer. When purchasing a particular media product for the first time, customers are advised to purchase small quantities to insure their expectations are met. The quality of Xerox supplies is consistent from ream to ream and is backed by a 100% guarantee such that if you are unhappy with the performance of recommended Xerox® Paper or Specialty Media, Domtar will either take back the unused product and replace it or refund your money. The quality of non-Xerox branded paper may vary from ream to ream or carton to carton, so for optimum performance on Xerox color equipment, use only the best: Xerox supplies.

To learn more about Xerox® Paper and Specialty Media, please call 1.800.458.4640, Prompt #1.

To learn more about the benefits of using Xerox Supplies (toner and ink), please contact your Xerox Supplies Representative at 1.800.822.2200 (U.S.) or 1.800.668.0199 (Canada).

Xerox® Color C60/C70 Press Recommended Media List

Item Number	Paper & Specialty Media Description	Size	gsm	Mode	Image Quality System Setting	Trays 1 - 4					Trays 6 - 7		Tray 5 (Bypass)	Additional Information
						1	2	3	4	HCF	OHCF			
Xerox® Vitality™ Multipurpose Printer Paper														
3R02047	20 lb. Bond	8.5 x 11	75	Plain	Plain A	A	A	A	A	A	A	A	A	
3R11415	20 lb. Bond	8.5 x 11 Xpress	75	Plain	Plain A	A	A	A	A	A	A	A	A	
3R02041	20 lb. Bond	8.5 x 11 3HP	75	Plain	Plain A	A	A	A	A	A	A	A	A	Select Hole Punched Paper Type to avoid false jams.
3R02051	20 lb. Bond	8.5 x 14	75	Plain	Plain A	A	A	A	A	A	A	A	A	
3R03761	20 lb. Bond	11 x 17	75	Plain	Plain A	A	A	A	A	A	A	A	A	
Xerox® Vitality™ Index Paper														
3R11747	90 lb. Index	8.5 x 11	163	Heavyweight 1	HW1C	A	A	A	A	A	A	A	A	
3R11748	90 lb. Index	17 x 11	163	Heavyweight 1	HW1C	A	A	A	A	A	A	A	A	
3R11749	110 lb. Index	8.5 x 11	199	Heavyweight 2		S	S	S	S	S	S	A	A	Increased jams may occur when auto-duplexing. Increased jams may occur when Output Format is Auto of Face Down. Us Face Up output format if this occurs. When feeding HW2 and/or coated stock it is highly recommended to feed from tray 5 (bypass) or tray 6/7 (OHCF) due to degraded feeding performance of trays 1-4.
Xerox® Bold™ Digital Printing Paper														
3R11540	24 lb. / 60 lb. Text	8.5 x 11	90	Plain	Plain B	A	A	A	A	A	A	A	A	
3R11541	24 lb. / 60 lb. Text	8.5 x 11 3HP	90	Plain	Plain B	A	A	A	A	A	A	A	A	On Light Production Finisher, do not staple more than 70 sheets per set. For 3HP, select Hole Punched Paper Type to avoid false jams.
3R11542	24 lb. / 60 lb. Text	8.5 x 14	90	Plain	Plain B	A	A	A	A	A	A	A	A	
3R11543	24 lb. / 60 lb. Text	11 x 17	90	Plain	Plain B	A	A	A	A	A	A	A	A	
3R11760	28 lb. / 70 lb. Text	8.5 x 11	105	Plain	Plain C	A	A	A	A	A	A	A	A	
3R11761	28 lb. / 70 lb. Text	8.5 x 11 3HP	105	Plain	Plain C	A	A	A	A	A	A	A	A	
3R20150	28 lb. / 70 lb. Text	8.5 x 14	105	Plain	Plain C	A	A	A	A	A	A	A	A	
3R11762	28 lb. / 70 lb. Text	17 x 11	105	Plain	Plain C	A	A	A	A	A	A	A	A	
3R11763	28 lb. / 70 lb. Text	18 x 12	105	Plain	Plain C	A	A	A	A	A	A	A	A	
3R11764	32 lb. / 80 lb. Text	8.5 x 11	120	Heavyweight 1	HW1A	A	A	A	A	A	A	A	A	
3R11765	32 lb. / 80 lb. Text	17 x 11	120	Heavyweight 1	HW1A	A	A	A	A	A	A	A	A	
3R11766	32 lb. / 80 lb. Text	18 x 12	120	Heavyweight 1	HW1A	A	A	A	A	A	A	A	A	
3R11767	60 lb. Cover	8.5 x 11	163	Heavyweight 1	HW1C	A	A	A	A	A	A	A	A	
3R11768	60 lb. Cover	17 x 11	163	Heavyweight 1	HW1C	A	A	A	A	A	A	A	A	
3R11770	80 lb. Cover	8.5 x 11	216	Heavyweight 2		S	S	S	S	S	S	A	A	Increased jams may occur when auto-duplexing. Increased jams may occur when Output Format is Auto of Face Down. Us Face Up output format if this occurs. When feeding HW2 and/or coated stock it is highly recommended to feed from tray 5 (bypass) or tray 6/7 (OHCF) due to degraded feeding performance of trays 1-4.
3R11771	80 lb. Cover	17 x 11	216	Heavyweight 2		S	S	S	S	S	S	A	A	
3R11772	80 lb. Cover	18 x 12	216	Heavyweight 2		S	S	S	S	S	S	A	A	
3R11774	100 lb. Cover	8.5 x 11	270	Heavyweight 4								S	M	
3R11775	100 lb. Cover	17 x 11	270	Heavyweight 4								S	M	
3R11776	100 lb. Cover	18 x 12	270	Heavyweight 4								S	M	
Xerox® Bold™ Digital Printing Paper, 30% Recycled														
3R20160	28 lb. / 70 lb. Text	8.5 x 11	105	Plain	Plain C	A	A	A	A	A	A	A	A	
3R20161	28 lb. / 70 lb. Text	17 x 11	105	Plain	Plain C	A	A	A	A	A	A	A	A	
3R20162	28 lb. / 70 lb. Text	18 x 12	105	Plain	Plain C	A	A	A	A	A	A	A	A	
3R20163	60 lb. Cover	8.5 x 11	163	Heavyweight 1	HW1A	A	A	A	A	A	A	A	A	
3R20164	60 lb. Cover	17 x 11	163	Heavyweight 1	HW1A	A	A	A	A	A	A	A	A	
3R20165	60 lb. Cover	18 x 12	163	Heavyweight 1	HW1A	A	A	A	A	A	A	A	A	
3R20166	80 lb. Cover	8.5 x 11	216	Heavyweight 2		S	S	S	S	S	S	A	A	Increased jams may occur when auto-duplexing. Increased jams may occur when Output Format is Auto of Face Down. Us Face Up output format if this occurs. When feeding HW2 and/or coated stock it is highly recommended to feed from tray 5 (bypass) or tray 6/7 (OHCF) due to degraded feeding performance of trays 1-4.
3R20167	80 lb. Cover	17 x 11	216	Heavyweight 2		S	S	S	S	S	S	A	A	
3R20168	80 lb. Cover	18 x 12	216	Heavyweight 2		S	S	S	S	S	S	A	A	
3R20169	100 lb. Cover	8.5 x 11	270	Heavyweight 4								S	M	
3R20170	100 lb. Cover	17 x 11	270	Heavyweight 4								S	M	

Xerox® Color C60/C70 Press Recommended Media List

Part Number	Description	Weight	Color	Surface	Weight	Weight	Weight	Weight	Weight	Weight	Weight	Weight
3R20171	100 lb. Cover	18 x 12	270	Heavyweight 4	A	A	A	A	A	A	S	M
Xerox® Bold™ Digital Printing Paper, 100% Recycled												
3R11815	28 lb./70 lb. Text	8.5 x 11	105	Recycled	A	A	A	A	A	A	A	A
Xerox® Bold™ Coated Gloss Digital Printing Paper												
3R11450	80 lb. Text	8.5 x 11	120	Coated 1	A	A	A	A	A	A	A	M
3R11451	80 lb. Text	17 x 11	120	Coated 1	A	A	A	A	A	A	A	M
3R11452	80 lb. Text	18 x 12	120	Coated 1	A	A	A	A	A	A	A	M
3R11443	80 lb. Text	19 x 13	120	Coated 1	A	A	A	A	A	A	A	M
3R11454	100 lb. Text	8.5 x 11	144	Coated 1	A	A	A	A	A	A	A	M
3R11455	100 lb. Text	17 x 11	144	Coated 1	A	A	A	A	A	A	A	M
3R11456	100 lb. Text	18 x 12	144	Coated 1	A	A	A	A	A	A	A	M
3R11444	100 lb. Text	19 x 13	144	Coated 1	A	A	A	A	A	A	A	M
3R11458	80 lb. Cover	8.5 x 11	210	Coated 2	S	S	S	S	S	S	A	M
3R11459	80 lb. Cover	17 x 11	210	Coated 2	S	S	S	S	S	S	A	M
3R11460	80 lb. Cover	18 x 12	210	Coated 2	S	S	S	S	S	S	A	M
3R11445	80 lb. Cover	19 x 13	210	Coated 2	S	S	S	S	S	S	A	M
3R11462	100 lb. Cover	8.5 x 11	280	Coated 3	S	S	S	S	S	S	A	M
3R11463	100 lb. Cover	17 x 11	280	Coated 3	S	S	S	S	S	S	A	M
3R11464	100 lb. Cover	18 x 12	280	Coated 3	S	S	S	S	S	S	A	M
3R11446	100 lb. Cover	19 x 13	280	Coated 3	S	S	S	S	S	S	A	M
3R11466	110 lb. Cover	8.5 x 11	300	Coated 3	S	S	S	S	S	S	A	M
3R11467	110 lb. Cover	17 x 11	300	Coated 3	S	S	S	S	S	S	A	M
3R11468	110 lb. Cover	18 x 12	300	Coated 3	S	S	S	S	S	S	A	M
Xerox® Bold™ Coated Stain Digital Printing Paper												
3R11470	80 lb. Text	8.5 x 11	120	Coated 1	A	A	A	A	A	A	A	M
3R11471	80 lb. Text	17 x 11	120	Coated 1	A	A	A	A	A	A	A	M
3R11472	80 lb. Text	18 x 12	120	Coated 1	A	A	A	A	A	A	A	M
3R11496	80 lb. Text	19 x 13	120	Coated 1	A	A	A	A	A	A	A	M
3R11474	100 lb. Text	8.5 x 11	144	Coated 1	A	A	A	A	A	A	A	M
3R11475	100 lb. Text	17 x 11	144	Coated 1	A	A	A	A	A	A	A	M
3R11476	100 lb. Text	18 x 12	144	Coated 1	A	A	A	A	A	A	A	M
3R11497	100 lb. Text	19 x 13	144	Coated 1	A	A	A	A	A	A	A	M
3R11478	80 lb. Cover	8.5 x 11	210	Coated 2	S	S	S	S	S	S	A	M
3R11479	80 lb. Cover	17 x 11	210	Coated 2	S	S	S	S	S	S	A	M
3R11480	80 lb. Cover	18 x 12	210	Coated 2	S	S	S	S	S	S	A	M
3R11518	80 lb. Cover	19 x 13	210	Coated 2	S	S	S	S	S	S	A	M
3R11482	100 lb. Cover	8.5 x 11	280	Coated 3	S	S	S	S	S	S	A	M
3R11483	100 lb. Cover	17 x 11	280	Coated 3	S	S	S	S	S	S	A	M
3R11484	100 lb. Cover	18 x 12	280	Coated 3	S	S	S	S	S	S	A	M
3R11519	100 lb. Cover	19 x 13	280	Coated 3	S	S	S	S	S	S	A	M
3R11486	110 lb. Cover	8.5 x 11	300	Coated 3	S	S	S	S	S	S	A	M
3R11487	110 lb. Cover	17 x 11	300	Coated 3	S	S	S	S	S	S	A	M
3R11488	110 lb. Cover	18 x 12	300	Coated 3	S	S	S	S	S	S	A	M
Xerox® Bold™ Super Gloss Cover												
3R11680	8 Point	8.5 x 11	170	Coated 2 or Heavyweight 2	S	S	S	S	S	S	S	M
3R11681	8 Point	17 x 11	170	Coated 2 or Heavyweight 2	S	S	S	S	S	S	S	M
3R11682	8 Point	18 x 12	170	Coated 2 or Heavyweight 2	S	S	S	S	S	S	S	M

Environmental conditions may require that coated paper be fed one sheet at a time through Tray 5 (By-pass). Relative humidity greater than 40% could cause multifeeds. OCHF prevents multifeeds better using Coated 2 when relative humidity is greater than 40%. Output may require removal at 25 sheets in the tray when not using a finisher. Gloss variation can occur from machine rolls, especially on high area coverage prints. Preference for Coated 1, Coated 2 or Heavyweight 2 may occur.

Increased jams may occur when Output Format is Auto or Face Down. Use Face Up Output

Environmental conditions may require that coated paper be fed one sheet at a time through Tray 5 (By-pass). Relative humidity greater than 40% could cause multifeeds. OCHF prevents multifeeds better using Coated 2 when relative humidity is greater than 40%. Output may require removal at 25 sheets in the tray when not using a finisher. Gloss variation can occur from machine rolls, especially on high area coverage prints. Preference for Coated 1, Coated 2 or Heavyweight 2 may occur.

Increased jams may occur when Output Format is Auto or Face Down. Use Face Up Output

Environmental conditions may require that coated paper be fed one sheet at a time through Tray 5 (By-pass). Relative humidity greater than 40% could cause multifeeds. OCHF prevents multifeeds better using Coated 2 when relative humidity is greater than 40%. Output may require removal at 25 sheets in the tray when not using a finisher. Gloss variation can occur from machine rolls, especially on high area coverage prints. Preference for Coated 1, Coated 2 or Heavyweight 2 may occur.

Increased jams may occur when Output Format is Auto or Face Down. Use Face Up Output

Xerox® Color C60/C70 Press Recommended Media List

Media ID	Media Name	Weight	Dimensions	Quantity	Coated 2 or Heavyweight 2	Coated 2B	S	S	S	S	M	M
3R11683	10 Point	8.5 x 11	219	Coated 2 or Heavyweight 2	Coated 2B	S	S	S	S	S	M	M
3R11684	10 Point	17 x 11	219	Coated 2 or Heavyweight 2	Coated 2B	S	S	S	S	S	M	M
3R11685	10 Point	18 x 12	219	Coated 2 or Heavyweight 2	Coated 2B	S	S	S	S	S	M	M
3R11686	12 Point	8.5 x 11	247	Coated 3 or Heavyweight 3	Coated 3A	S	S	S	S	S	M	M
3R11687	12 Point	17 x 11	247	Coated 3 or Heavyweight 3	Coated 3A	S	S	S	S	S	M	M
3R11688	12 Point	18 x 12	247	Coated 3 or Heavyweight 3	Coated 3A	S	S	S	S	S	M	M
Xerox® Revolution NeverTear™												
3R20172	5 mil	8.5 x 11	135	Coated 1	Coated 1B	A						
3R20173	5 mil	8.5 x 11 3HP	135	Coated 1	Coated 1B	A						
3R20174	5 mil	11 x 17	135	Coated 1	Coated 1B	A						
3R20176	8 mil	8.5 x 11	230	Coated 3	Coated 3A	M						
3R20185	8 mil Pre-Scored Horizontal	8.5 x 11	230	Coated 3	Coated 3A	M						
3R20186	8 mil Pre-Scored Vertical	8.5 x 11	230	Coated 3	Coated 3A	M						
3R20187	8 mil Pre-Perforated Shelf Tags	8.5 x 11	230	Coated 3	Coated 3A	M						
3R20188	8 mil Pre-Perforated Door Hangers	8.5 x 11	230	Coated 3	Coated 3A	M						
3R20189	8 mil Pre-Perforated Luggage Tags	8.5 x 11	230	Coated 3	Coated 3A	M						
3R20190	8 mil Pre-Perforated Badges	8.5 x 11	230	Coated 3	Coated 3A	M						
3R20191	8 mil Pre-Perforated ID Cards	8.5 x 11	230	Coated 3	Coated 3A	M						
3R20192	8 mil Pre-Perforated Parking Passes	8.5 x 11	230	Coated 3	Coated 3A	M						
3R20193	8 mil Pre-Perforated Portrait Badges	8.5 x 11	230	Coated 3	Coated 3A	M						
Xerox® Revolution™ ID Cards												
3R20077	2-Side Laminated with Perf-Out, 1-Up	8.5 x 11	172	Heavyweight 1	HW1C	A						
3R20078	2-Side Laminated with Perf-Out, 2-Up	8.5 x 11	172	Heavyweight 1	HW1C	A						
3R14733	1-Side Laminated with Peel-Off, 1-Up	8.5 x 11	178	Heavyweight 2	HW2B	A						
3R14734	1-Side Laminated with Peel-Off, 2-Up	8.5 x 11	178	Heavyweight 2	HW2B	A						
3R14735	1-Side Laminated with Microper-Out, 1-Up	8.5 x 11	174	Heavyweight 2	HW2B	A						
3R14736	1-Side Laminated with Microper-Out, 2-Up	8.5 x 11	174	Heavyweight 2	HW2B	A						
3R14714	7 mil Synthetic with Peel-Off, 1-Up	8.5 x 11	185	Heavyweight 1	HW1B	A						
3R14716	7 mil Synthetic with Peel-Off, 2-Up	8.5 x 11	185	Heavyweight 1	HW1B	A						
Xerox® Revolution™ Carbonless – Premium Digital												
3R12420	2-Part Straight/Reverse	8.5 x 11	80	Plain	Plain A	S	S	S	S	S	S	S
3R12422	2-Part Straight/Reverse	8.5 x 14	80	Plain	Plain A	S	S	S	S	S	S	S
3R12423	2-Part Straight/Reverse	11 x 17	80	Plain	Plain A	S	S	S	S	S	S	S
3R12421	2-Part Straight/Reverse	8.5 x 11	80	Plain	Plain A	S	S	S	S	S	S	S
3R12424	3-Part Reverse	8.5 x 11	80	Plain	Plain A	S	S	S	S	S	S	S
3R12425	3-Part Straight	8.5 x 11	80	Plain	Plain A	S	S	S	S	S	S	S
3R12427	3-Part Straight	8.5 x 14	80	Plain	Plain A	S	S	S	S	S	S	S
3R12426	3-Part Straight (Mini Carton)	8.5 x 11	80	Plain	Plain A	S	S	S	S	S	S	S
3R12429	4-Part Reverse	8.5 x 11	80	Plain	Plain A	S	S	S	S	S	S	S
3R12430	4-Part Straight	8.5 x 11	80	Plain	Plain A	S	S	S	S	S	S	S
3R12434	Singles CB	8.5 x 11	80	Plain	Plain A	S	S	S	S	S	S	S
3R12435	Singles CFB	8.5 x 11	80	Plain	Plain A	S	S	S	S	S	S	S
3R12437	Singles CFB	8.5 x 11	80	Plain	Plain A	S	S	S	S	S	S	S
3R12439	Singles CF	8.5 x 11	80	Plain	Plain A	S	S	S	S	S	S	S
Xerox® Revolution™ Label												

Format if this occurs. C1S media should not be autocluplexed.

Environmental conditions may require that coated paper be fed one sheet at a time through Tray 5 (Bypass). Relative humidity greater than 40% could cause multifeeds. OCHF prevents multifeeds better using Coated 2 when relative humidity is greater than 40%. Output may require removal at 25 sheets in the tray when not using a finisher. Glass variation can occur from machine rolls, especially in high area coverage prints. Preference for Coated 3 or Heavyweight 3 may occur. Increased jams may occur when Output Format is Auto or Face Down. Use Face Up Output. Format if this occurs. C1S media should not be autocluplexed.

Run less than 50 sheets to stacker. Remove and fan or allow to cool stacked horizontally.

Run less than 50 sheets to stacker

Load Tray 5 (Bypass) LEF (Long Edge Feed)

Remove and fan or allow to cool stacked horizontally

Deletions may occur if imaged near the edges of the card

Deliver to the Offset Catch Tray

Load Tray 1 LEF (Long Edge Feed) with cards toward the back of the tray (inboard)

Not intended for extensive/exclusive usage

Deletions may occur if imaged near the edges of the card

Deliver to the Offset Catch Tray

Load Tray 5 (Bypass) SEF (Short Edge Feed) with cards on the trailing edge

Not intended for extensive/exclusive usage

Deletions may occur if imaged near the edges of the card

Deliver to the Offset Catch Tray

Load Tray 5 (Bypass) SEF (Short Edge Feed) with cards on the trailing edge

Load/stack no more than 80 sheets at a time

Not intended for extensive/exclusive usage

Carbonless paper is not intended for extensive or exclusive usage. Limit monthly volumes. It is recommended to use equipment with an Offset Catch Tray, rather than a finishing device.

Xerox® Color C60/C70 Press Recommended Media List

Part Number	Description	Weight	Dimensions	Quantity	Label	Orientation	Material	Notes
3R12735	Gloss Coated 1-Up, Die Cut	205	8.5 x 11		Label	S	S	
3R12736	Gloss Coated 1-Up, Full Sheet	205	8.5 x 11		Label	S	S	Labels are not intended as sole application of machine. Do not stack large amounts in Output Tray.
3R12737	Gloss Coated 4-Up	205	8.5 x 11		Label	S	S	
3R12740	Gloss Coated 10-Up	205	8.5 x 11		Label	S	S	
3R12741	Gloss Coated 30-Up	205	8.5 x 11		Label	S	S	
3R05772	Matte Coated 1-Up, Die Cut	205	8.5 x 11		Label	S	S	
3R12371	Matte Coated 1-Up, Full Sheet	205	8.5 x 11		Label	S	S	
3R05773	Matte Coated 4-Up	205	8.5 x 11		Label	S	S	Labels are not intended as sole application of machine. Do not stack large amounts in Output Tray.
3R06332	Matte Coated 10-Up	205	8.5 x 11		Label	S	S	
3R06333	Matte Coated 30-Up	205	8.5 x 11		Label	S	S	
3R06330	Matte Coated 2-Up, CD/DVD	205	8.5 x 11		Label	S	S	
3R14626	4 mil Vinyl with Permanent Adhesive	350	8.5 x 11		Coated 1			Load Tray 5 LEF (Long Edge Feed)
3R14627	4 mil Vinyl with Permanent Adhesive	350	12 x 18		Coated 1			Load Tray 5 LEF (Long Edge Feed)
3R14628	4 mil Vinyl with Removable Adhesive	350	8.5 x 11		Coated 1			
3R14629	4 mil Vinyl with Removable Adhesive	350	12 x 18		Coated 1			
Xerox® Revolution™ Mailing Media								
3R12445	Business Reply Envelope	195	8.5 x 11		Heavyweight 2			Load reply envelope Face Up in Tray 6, 7 (750 Sheets Maximum) & Bypass (Tray 5) with Envelope portion leading. Face Down in Tray 1, 2, 3 & 4
Xerox® Revolution™ Tabs – Plain Paper								
3R20113	90 lb. Index, Single Straight	163	9 x 11		Tab Stock 1			
3R04417	90 lb. Index, Single Straight	163	9 x 11		Tab Stock 1	Tab 1C		
3R04418	90 lb. Index, Single Straight	163	9 x 11 3HP		Tab Stock 1	Tab 1C		
3R04407	90 lb. Index, Single Position 1 & 5	163	9 x 11		Tab Stock 1	Tab 1C		
3R04409	90 lb. Index, Single Position 2 & 4	163	9 x 11		Tab Stock 1	Tab 1C		
3R04411	90 lb. Index, Single Position 3	163	9 x 11		Tab Stock 1	Tab 1C		
3R05422	90 lb. Index, Single Reverse	163	9 x 11		Tab Stock 1	Tab 1C		
3R05423	90 lb. Index, Single Reverse	163	9 x 11 3HP		Tab Stock 1	Tab 1C		
3R05426	90 lb. Index, Single Reverse	163	9 x 11		Tab Stock 1	Tab 1C		
3R05427	90 lb. Index, Single Reverse	163	9 x 11		Tab Stock 1	Tab 1C		
3R04415	90 lb. Index, Single Reverse	163	9 x 11		Tab Stock 1	Tab 1C		
3R04416	90 lb. Index, Single Reverse	163	9 x 11 3HP		Tab Stock 1	Tab 1C		
3R05713	90 lb. Index, Single Reverse	163	9 x 11		Tab Stock 1	Tab 1C		
3R05714	90 lb. Index, Single Reverse	163	9 x 11 3HP		Tab Stock 1	Tab 1C		
Xerox® Revolution™ Mailing Media								
3R12407	Presentation Folder, 10 Point		12 x 18		Coated 2 or Heavyweight 2			
3R03117	Transparency for Monochrome Print, Clear	219	8.5 x 11		Transparency			
3R03108	Transparency with Removable Stripe		8.5 x 11		Transparency			It is not recommended to output more than 20 transparencies at a time. If the job is larger than 20 pages, use Transparency Separator feature.
3R12505	Transparency for Color Printing, Clear		8.5 x 11		Transparency			
Xerox® Revolution™ Mailing Media								
3R14731	Integrated Card, 60 lb. Cover	165	8.5 x 11		Heavyweight 3			Load MSI/Bypass Tray 5 in LEF (Long Edge Feed) orientation with cards on trailing edge. No more than 75 sheets should be loaded in feed tray at one time. Select Face Up delivery to the Offset Catch Tray. Stack no more than 75 sheets in Offset Catch Tray. Not intended for extensive/exclusive use.
3R14732	Integrated Card, C1S	163	8.5 x 11		Coated 3			Load individual sheets into MSI/Bypass Tray 5 in LEF (Long Edge Feed) orientation. Not intended for extensive/exclusive use.
3R14689	Lightweight Gloss		8.5 x 11		Coated 3 Reload			



Domtar is the exclusive trademark licensee of the Xerox® Paper and Specialty Media Line within the United States and Canada.

Working collaboratively with the Xerox Corporation and our Media Partners, Domtar designs and manufactures the Xerox® Paper and Specialty Media line to bring you the most extensive line of digitally optimized products in the United States and Canada.

With the Domtar Performance Guarantee, you can be assured that if you are unhappy with the performance of the product, you may return the unused portion and Domtar will either replace it, or refund your money.

Xerox® Paper and Specialty Media products are widely available for purchase through office supply dealers, paper merchants, office supply stores, online as well as in selected retail stores.

www.domtar.com
www.xeroxpaperUSA.com
www.xeroxpaper.ca